

#### HDS 10/20-4 MX

The HDS 10/20-4 MX with hose reel, 20-metre pressure hose and 4-pole, water-cooled electric motor is the most powerful three-phase hot water high-pressure cleaner in the Kärcher Middle class.

















#### 1 Efficiency

- In the ecolefficiency mode the machine operates in the most economical temperature range (60°C) with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full-load operation.

#### 2 Maximum efficiency

- Highly efficient, tried-and-tested burner technology.
- Four-pole electric motor with three-piston axial pump.

#### 3 Operational safety

- The large, integrated water fine filter reliably protects the high-pressure pump against small dirt particles.
- An integrated exhaust gas thermostat switches off the drive motor if the emission temperature exceeds 300°C.

#### 4 Storage

- Integrated hose reel with 20 m pressure hose. For a large operating radius and effortless stowage.
- Spacious storage compartment for cleaning agents, gloves or tools.

### **TECHNICAL DATA AND EQUIPMENT**





#### HDS 10/20-4 MX

- Economical eco!efficiency mode
- Two detergent tanks
- Three-phase motor: water-cooled

Technical data				
Order No.		1.071-912.0		
EAN code		4054278140346		
Supply voltage	Ph/V/Hz	3 / 400 / 50		
Flow rate	l/h	500-1000		
Pressure	bar / MPa	30-200 / 3-20		
Max. temperature	°C	80 / 155		
Connection load	kW	7.8		
Heating oil or gas consumption, full load	kg/h	6.4		
Fuel tank	1	25		
Weight	kg	179		
Dimensions (L × W × H)	mm	1330 × 750 × 1060		
Equipment				
Spray gun		EASY!Force Advanced	Pole reverse plug (3-phase)	
High-pressure hose	m	20 / Long-life	Service electronics with LED display	
Spray lance	mm	1050	Two detergent tanks	•
Power nozzle			Dry-running protection	

Equipment				
Spray gun		EASY!Force Advanced	Pole reverse plug (3-phase)	
High-pressure hose	m	20 / Long-life	Service electronics with LED display	
Spray lance	mm	1050	Two detergent tanks	
Power nozzle			Dry-running protection	
Servo Control		-		
Integrated pressure hose reel				
Anti-twist system (AVS)		-		
Tanks for cleaning agent, calcification protection and fuel can be filled from the outside		•		
Control panel with display light				
Three-piston axial pump		With ceramic pistons		
Pressure cut-off		-		

■ Included in delivery.



























				Max. working			
		Order No.	ID	pressure	Length	Price	Description
Standard with unions on both sides		I.					
High-pressure hose 2x EASY!Lock,	1	6.110-031.0	ID 8	315 bar	10 m		High-pressure hose (ID 8) suitable for up to 315 bar pres-
ID 8, 315 bar, 10 m, ANTI!Twist							sure. High-pressure hose with innovative EASY!Lock hand
High procesure has 2y FACVII only		6.110-030.0	ID 8	315 bar	15 m		screw connection at both ends, ANTI!Twist, 10 m long.
High-pressure hose 2x EASY!Lock, ID 8, 315 bar, 15 m, ANTI!Twist	2	6.110-030.0	100	212 ngi	13 111		15 m long high-pressure hose, ID 8, with ANTI!Twist at both ends with time-saving EASY!Lock hand screw connection.
High-pressure hose 2x EASY!Lock	3	6.110-032.0	ID 8	315 bar	20 m		High-pressure hose (ID 8), 20 m long, with time-saving and
ID 8, 315 bar, 20 m, ANTI!Twist							robust EASY!Lock hand screw connection at both ends. For
							up to 315 bar pressure.
High-pressure hose 2x EASY!Lock, ID 8, 315 bar, 30 m, ANTI!Twist	4	6.110-014.0	ID 8	315 bar	30 m		Convenient length (30 m) and innovative EASY!Lock hand screw connection: high-pressure hose (ID 8) with ANTI!Twist
0, 515 bai, 50 iii, Aivii:1Wist							for up to 315 bar pressure.
High-pressure hose 2x EASY!Lock,	5	6.110-042.0	ID 10	220 bar	15 m		With innovative EASY!Lock hand screw connection for up to
ID 10, 220 bar, 15 m							220 bar pressure: 15 m long high-pressure hose (ID 10).
High-pressure hose 2x EASY!Lock,	6	6.110-043.0	ID 10	220 bar	20 m		Main features of this high-pressure hose (ID 10): 20 m long
ID 10, 220 bar, 20 m							with extremely time-saving and convenient EASY!Lock hand screw connection at both ends.
High-pressure hose 2x EASY!Lock,	7	6.110-044.0	ID 10	220 bar	25 m		Impressive values and basic equipment: high-pressure hose,
ID 10, 220 bar, 25 m	-						(ID 10), 25 m long, for up to 220 bar pressure.
High-pressure hose 2x EASY!Lock,	8	6.110-045.0	ID 10	220 bar	40 m		40 m long high-pressure hose with EASY!Lock system for
ID 10, 220 bar, 40 m							time-saving hand screw connection (at both ends). (ID) 10,
High-pressure hose 2x EASY!Lock,	9	6.110-059.0	ID 12	250 bar	15 m		up to 220 bar working pressure.  Suitable for up to 250 bar working pressure: high-pressure
ID 12, 250 bar, 15 m	Э	0.110 033.0	10 12	250 bai	13111		hose (ID 12), 15 m long, with convenient EASY!Lock hand
							screw connection at both ends.
High-pressure hose 2x EASY!Lock	10	6.110-060.0	ID 12	250 bar	40 m		With EASY!Lock hand screw connection, 40 m long for wide
2x EASY!Lock ID 12, 250 bar, 40 m							working radius: high-pressure hose (ID 12) with EASY!Lock hand screw connection at both ends. Suitable for up to 250
							bar working pressure.
Longlife 400 with unions on both si	des						
High-pressure hose Longlife 400	11	6.110-023.0	ID 8	400 bar	30 m		Durable high-pressure hose with double steel reinforcement,
2x EASY!Lock, ID 8, 400 bar, 30 m,							ANTI!Twist and EASY!Lock hand screw connection at both
ANTI!Twist High-pressure hose Longlife 400	12	6.110-027.0	ID 8	400 bar	20 m		ends. ID 8, 30 m long, for up to 400 bar pressure.  High-pressure hose with ANTI!Twist, EASY!Lock hand screw
2x EASY!Lock, ID 8, 400 bar, 20 m,	12	0.110-027.0	100	400 bai	20 111		connections and double steel reinforcement. 20 m long, ID 8,
_ANTI!Twist							EASY!Lock hand screw connection at both ends.
High-pressure hose Longlife 400	13	6.110-029.0	ID 8	400 bar	15 m		The double steel reinforcement ensures a long lifetime of
2x EASY!Lock, ID 8, 400 bar, 15 m, ANTI!Twist							this 15 m long high-pressure hose (ID 8), approved for up to
Food industry version with unions	on hot	h sides					400 bar pressure hose.
High-pressure hose, food grade, 2x		6.110-051.0	ID 8	250 bar	10 m		High-pressure hose (ID 8), 10 m long, with grey, non-mark-
EASY!Lock, ID 8, 10 m, ANTI!Twist				1			ing outer covering. Approved for use in the food industry.
							With quick and robust EASY!Lock hand screw connection at
High processes have food avail- 200	1 -	6 110 053 0	ID 0	250 bar	20 m		both ends.
High-pressure hose, food grade, 2x EASY!Lock, ID 8, 20 m, ANTI!Twist	15	6.110-052.0	ID 8	250 bar	20 m		Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, AN-
							TI!Twist and EASY!Lock hand screw connections.
Longlife food design with screw cor	nectio	ons at both ends					
High-pressure hose, food grade	16	6.110-053.0	ID 8	400 bar	10 m		With blue, non-marking and animal fat resistant outer cov-
Longlife, 400 2x EASY!Lock, ID 8,							ering: durable high-pressure hose (ID 8), 10 m long, AN-
_10 m, ANTI!Twist							TI!Twist and EASY!Lock hand screw connection at both ends.

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.









		Order No.	ID	Max. working pressure	Length	Price	Description
Longlife 400 High-pressure hose Longlife 400 AVS hose reel connection, ID 8, 400 bar, 20 m, ANTI!Twist	17	6.110-028.0	ID 8	400 bar	20 m		20 m high-pressure hose (ID 8), for up to 400 bar pressure. With AVS hose reel connection and double steel reinforcement. EASY!Lock hand screw connection at other end of the hose.
Standard High-pressure hose AVS hose reel connection, ID 8, 315 bar, 15 m, ANT!!Twist	18	6.110-033.0	ID 8	315 bar	15 m		High-pressure hose with rotatable ANTI!Twist AVS hose reel connection and EASY!Lock hand screw connection. Maximum working pressure 315 bar, 15 m long, ID 6.
Special hoses High-pressure hose 1x EASY!Lock curved 1x M 22 x 1.5, ID 8, 400 bar, 1.5 m	19	6.110-068.0	ID 8	400 bar	1.5 m		For connection to hose reels: high-pressure hose, with M 22 × 1.5 connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure.

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.











		Order No.	Flow rate		Price	Description
Trigger guns				'		
EASY!Force Advanced	1	4.118-005.0				Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
Servo control						
Servo Control controller with EASY!Lock	2	4.118-008.0	750-1100 l/h			-
Quick connect						
Quick coupling	3	2.115-000.0				For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.
Male coupling	4	2.115-001.0				Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.





		Order No.	Nozzle size		Price	Description
Power nozzle spray angle 25°						
Power nozzle spray angle 25°	1	2.113-024.0	52			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°						
High-pressure nozzle with 0° spray angle	2	2.113-035.0	55			High-pressure nozzle with powerful jet for extremely stubborn dirt.
Power nozzle spray angle 15°						
Power nozzle spray angle 15°	3	2.113-047.0	55			Fan jet nozzle with 15° spray angle suitable for stubborn dirt.
Power nozzle spray angle 40°						
Power nozzle spray angle 40°	4	2.113-055.0	55			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.





	1	I	1	1	T			$\top$
		Order No.	Max. working pressure	Length		Price	Description	
		Order No.	pressure	Length		File	Description	L
Rotating spray lances	1	ı	1	ı				
1050 mm spray pipe, rotatable	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo-	- 1
							nomic handle for ease of use and protection. Rotatable 360 under pressure.	ľ
Spray lance, 200 mm, rotatable	2	4.112-027.0	300 bar	250 mm			600 mm stainless steel lance (manual coupling) with ergo-	
Spray lance, 400 mm, rotatable	3	4.112-024.0	300 bar	400 mm			nomic handle for ease of use and protection. Rotatable 360	
600 mm spray pipe, rotatable	4	4.112-007.0	300 bar	600 mm			under pressure.	
850 mm spray pipe, rotatable	5	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergo-	+
oso min spray pipe, rotatable			300 501	0.10.11111			nomic handle for ease of use and protection. Rotatable 360	۔ ا
							under pressure.	
1550 mm spray pipe, rotatable	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo-	
							nomic handle for ease of use and protection. Rotatable 360	°   [
	_						under pressure.	+
2050 mm spray pipe, rotatable	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo-	
							nomic handle for ease of use and protection. Rotatable 360 under pressure.	-
Double lance							onder pressore.	Ť
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on	Т
							handle at full water flow rate. Suitable for agricultural use (	
							e.g. stable cleaning).	
Angular spray lance								
Spray lance for toilets and rain	9	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe-	
gutters							cially shaped for effective and hygienic cleaning of gutters	
							and toilets.	_
Flexible spray lance	1 10	4.112-035.0	210 hav	1050 mm		1	1050 mm flouible lance with waviable hand from 20° to	Т
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance	-						140 , ideal for eleaning difficult to reach dreas, e.g. gotters.	Ħ
Telescopic spray lance	11	4.112-037.0	225 bar	5400 mm			Can be continuously extended from 1.8 to 5.4 m. For clean-	Т
							ing areas that are difficult to reach, such as ceilings or fa-	
							cades. With integrated HD trigger gun, M 22 x 1.5 connec-	
							tion with rotary coupling. Connection for M 18 x 1.5 nozzle	ŝ.
Strap for telescopic spray pipe	12	6.373-987.0					Convenient strap for relief when working with the telescop	- 1
							ic spray lance (6.394-690). The burden is optimally distrib-	
Gutter cleaner							uted on the body and longer periods of use are possible.	_
Gutter cleaning lance	13	2.112-015.0	1				The lance is suited for cleaning of gutter systems. Because	Т
dotter cleaning lance	13	2.112 013.0					of the shape of the lance and the special nozzle the gutter	
							can be cleaned without removing the cover plates.	
Undercarriage spray lance								
Underbody lance	14	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle			•			-		
Additional handle for EASY!Lock	15	4.321-380.0						L
spray lances								
Weed control								
WR 50 trapezoidal thread	_	2.114-013.0						
WR 20 trapezoidal thread	17	2.114-014.0						

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.













		Order No.				Price	Description	
Crane lifting kit			'	'				
Crane loading attachment kit for HDS medium and super class	1	2.642-424.0					Effortless loading by crane.	
Grey wheel kit								
Grey wheel kit HDS M/S	2	2.641-975.0						
Flame monitoring attachment kit								
Flame monitoring attachment kit for HDS M/S	3	2.641-796.0					More safety thanks to ABS HDS M/S flame monitoring system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.	
Y distributor			,					
Y distributor	4	4.111-024.0						
Accumulator kits								
Add-on accumulator for HDS M/S	5	2.641-803.0					The accumulator can be mounted on the HDS machine in order to dampen pressure surges, which conserves the machine's line system.	
Remote control set								
Remote control attachment kit, HDS-M class	6	2.642-157.0						
Coin-op remote control								
Coin remote control attachment kit, HDS-M class	7	2.642-158.0						

 $<sup>\</sup>blacksquare$  Included in delivery.  $\hfill\Box$  Available accessories.  $\hfill \blacktriangle$  Extension hose.





















		Order No.	Flow rate	Nozzle size	Diame- ter	Price	Description
Hard Surface Cleaner FRV 30		<u>'</u>	•				
Hose fastening attachment kit	1	2.642-528.0					
Dirt trap attachment kit	2	2.642-532.0					
FR 30 Me surface cleaner							
Hard Surface Cleaner FR 30 Me	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard Surface Cleaner FR 50							
Surface Cleaner FR 50 Me	4	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kits for FR	1						
Nozzle kit for surface cleaners	5	2.640-442.0	850-1100 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).
Machine-specific nozzle kits for FR	V						
Nozzle kit 080 - for FRV	6	2.642-982.0		80			
FRV 30 Me surface cleaner							
Extension hose FRV 30 Me and FRV 50 Me	7	4.441-040.0					
Surface Cleaner FRV 30 Me	8	2.111-012.0					
Surface Cleaner FR 50 Me							
Surface Cleaner FRV 50 ME	9	2.111-024.0					

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.































		T	1	1	1		1	
		Order No.					Price	Description
Nozzle union								
Protection part TR only for re- placement	1	4.112-011.0						
Coupling parts			1					,
Articulated joint	2	6.987-705.0						This articulated joint with variable angle adjustment (up to an angle of 120°) is recommended for cleaning hard to reach areas. Fits directly on the spray lance.
Rotary coupling				,				
Rotary coupling	3	4.111-021.0						Reliably prevents twisting of HP hoses. Connection M 22 x 1.5 m. Handle protection
Coupling		14444 0070						For connecting and outcoding UD harves 2 v. M 22 v. 4.5
Connector	4	4.111-037.0						For connecting and extending HP hoses, 2 x M 22 x 1.5 m connection, brass with rubber protection
Connector  Screw sockets for surface cleaners	5	4.111-022.0		I		ı	I	For attaching high-pressure nozzles and accessory parts to
and Servo Control controller	5	4.111-022.0						the HD trigger gun (with nozzle screws) - 1 x M 22 x 1.5/1 x M 18 x 1.5.
Short spray unit	6	4.111-038.0						
EASY!Lock adapter			1					,
Adapter 1 M22 x 1.5 AG - EASY!Lock 22 AG	7	4.111-029.0						Adaptor for connecting pressure hoses with EASY!Lock and pressure hoses with M 22×1.5 connection.
Adapter 2 M22 x 1.5 IG - EASY!Lock 22 AG	8	4.111-030.0						Adaptor for connecting high-pressure cleaners or high-pressure guns with M 22 × 1.5 connection and pressure hoses with EASY!Lock.
Adapter 3 M22 x 1.5 IG - EASY!Lock 22 AG	9	4.111-031.0						Adaptor for connecting high-pressure guns with M 22×1.5 connection and spray lances or Servo Control controllers with EASY!Lock.
Adapter 4 EASY!Lock 22 IG - AVS	10	4.111-032.0						Adaptor for connecting pressure hoses with AVS swivel connection and EASY!Force high-pressure gun.
Adapter 5 EASY!Lock 22 IG - M22 x 1.5 AG	11	4.111-033.0						Adaptor for connecting EASY!Force high-pressure gun and spray lances with M 22 × 1.5 connection.
Adapter 6 EASY!Lock 22 IG - M22 x 1.5 AG	12	4.111-034.0						Adaptor for connecting pressure hoses with M 22×1.5 connection and EASY!Force high-pressure gun or high-pressure cleaners with EASY!Lock.
Adapter 7 M18 x 1.5 IG - EASY!Lock 20 AG	13	4.111-035.0						Adaptor for connecting spray lances with M 18 × 1.5 connection and nozzles, surface cleaners or wash brushes with EASY!Lock.
Adapter 8 EASY!Lock 20 IG - M18 x 1.5 AG	14	4.111-036.0						Adaptor for connecting nozzles, surface cleaners or wash brushes with M 18 × 1.5 connection and spray lances with EASY!Lock.
Flue pipe		1			1			E. O EOCH.
Flue gas adapter		4.656-149.0						Flue gas adapter with draught damper for flue pipe connec-
	16	4.656-080.0						tion (adapter for HDS burners for connection to a stack system).
Cleaning agent injector		1	'	1				- Systemy.
Stainless steel injector kit for HDS 10/20-4M	17	6.645-762.0						Developed for the HD 10/20-4 M High-pressure cleaner, the stainless steel injector ensures optimal cleaning agent dosage. Supplied with suction hose and filter.
Dosing valve for stainless steel injector	18	6.500-000.0						Retrofittable dosing valve for stainless steel injectors. For easy, convenient and precise cleaning agent dosing adjustment via a control knob.







		Order No.			Price	Description
Machine-specific nozzle kit with or	der no	. 3.637-170.0				
Nozzle kit 1,000 - 1,200 l/h	19	4.769-048.0				For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HP power nozzle + union
Nozzle insert with order no. 3.637-	001.0					
Nozzle insert up to 1,100 l/h - high pressure	20	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.
Nozzle insert up to 1,100 l/h - low pressure	21	4.769-001.0				For low pressure with machines up to 1.100 l/h

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.  $\ \, \blacktriangle$  Extension hose.

























		ı	1	T	1		T	_
			Max. working		Diame-			
		Order No.	pressure	Nozzle size	ter	Price	Description	
Barrel and tank cleaning			,					
Barrel cleaner BC 14/12	1	2.112-020.0					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachmen 4.115-000.0   4.115-006.0.	t $\square$
HKF 50 spray head, brass			,				,	
HKF 50 spray head, brass	2	3.631-039.0					Depth of immersion 850 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally	
	3	3.631-058.0					Depth of immersion 150 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally	
Nozzle kit for spray head HKF 50 (3	.631-	009.0 / 3.631-03	9.0)					
Nozzle 030 for 2-nozzle operation HKF 50	4	6.415-444.0		30			Nozzle for dual-nozzle operation	
Nozzle 090 for 1-nozzle operation HKF 50	5	6.415-447.0		90			Nozzle for single-nozzle operation	
Cone for plugging into bungholes	6	4.132-002.0					Cone for plugging into bungholes	
Double grip for precise control of spray head	7	2.863-036.0					Double handle. Precise control of the spray head	
Screw plug for using a spray head with one nozzle	8	5.411-061.0					Screw plug for using a spray head with one nozzle	
Nozzle 070 for HKF 50	9	6.415-077.0		70			Nozzle for dual-nozzle operation	
Pipe cleaning hose, ID 6			,					
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	10	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection fo nozzle R 1/8).	r 🗆
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	11	6.110-008.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection fo nozzle R 1/8).	r 🗆
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	12	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection fo nozzle R 1/8).	r 🗆
Pipe cleaning nozzle								
Pipe cleaning dirt blaster D 25 / 060	13	6.415-945.0		60	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the	
Pipe cleaning dirt blaster D 30 / 060	14	6.415-947.0		60	30 mm		necessary forward movement, as well as convenient handling.	
Pipe cleaning dirt blaster D 35 / 060	15	6.415-949.0		60	35 mm			
Pipe cleaning nozzle 120	16	5.763-089.0		120	16 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	17	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various je	t 🔲
	18	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	19	5.763-021.0		70	30 mm		30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes.	





		Order No.	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Rotating pipe cleaning nozzle	20	6.415-440.0		65	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	

lacktriangle Included in delivery.  $\Box$  Available accessories. lacktriangle Extension hose.







		Order No.	Max. working pressure	Nozzle size		Price	Description
<b>Angled vario nozzle 0-90°</b> Spezial nozzle 0005	1	4.113-007.0		50			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.
<b>Dirt blaster, large</b> Dirt blaster	2	4.114-036.0	300 bar	55			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.









		1		1					_
		Order No.	Nozzle size				Price	Description	
Wet blasting attachment (without n	ozzle)		•		'	'			
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0						Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle kits for wet jet unit									
Nozzle kit for wet jet unit 055	3	2.637-903.0	55					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.	
Boron carbide nozzle									
Boron carbide nozzle, for machines up to 1,000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	

 $<sup>\</sup>blacksquare$  Included in delivery.  $\hfill\Box$  Available accessories.  $\hfill \triangle$  Extension hose.













		Order No.	Flow rate		Price	Description
Cup foam lance			'			
Cup foam lance Advanced 025	1	2.112-017.0				Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.
1-litre cleaning agent container for foam lance	2	6.414-954.0				
Inno Foam Kit						
Inno Foam Set	3	2.112-008.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set	4	2.112-011.0				HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 090 for Inno / Easy Set 700-1,000 l/h	5	2.111-019.0	700-1000 l/h			Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.
Foam nozzle mounting kit						
Foam nozzle attachment kit	6	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.





















		Order No.	Length			Price	Description	
Automatic, self-winding hose reels					l			
ABS automatic hose drum HDS M/S	1	2.110-011.0	20 m				Automatic hose reel as a complete attachment kit that's easy to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose.	0
ABS holder, automatic hose drum HDS M/S	2	2.643-040.0						
Automatic hose reel, powder-coated steel / plastic	3	6.392-074.0	20 m				Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / syn- thetic material hose drum	4	6.392-083.0	20 m				Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated	5	6.392-106.0	20 m				Automatic hose reel of durable plastic. Painted steel bracket Suitable for 20 m high-pressure hose.	
Add-on kit hose reel lacquered basaltgra	6	6.392-105.0	20 m					
Automatic hose reel, stainless steel, includes swivel holder	7	6.392-076.0	20 m				Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS automatic stainless steel hose drum	8	6.392-122.0	20 m				High-grade, automatic steel hose reel. Especially suitable fo use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Powder-coated swivel holder	9	2.639-931.0					Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel.	ż. 🗆
Pivoting stainless steel wall brack- et attachment kit	10	2.641-867.0					Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.











		Order No.	Flow rate	Inlet tempera- ture	Length	Length	Price	Description		
Solar cleaning - telescopic lances					'					
iSolar TL 14 C (without hose)	1	4.110-002.0		max. 60 °C				Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick-release couplings for easy extension and retraction.		
iSolar TL 10 C (without hose)	2	4.110-007.0		max. 60 °C						
iSolar TL 10 H (without hose)	3	4.110-003.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction.		
iSolar TL 7 H (without hose)	4	4.110-004.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction.		
iSolar HP hose 7	5	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod		
iSolar HP hose 10	6	6.392-977.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod		
iSolar HP hose 14	7	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod		

<sup>■</sup> Included in delivery. □ Available accessories. ▲ Extension hose.









		Order No.	Flow rate		Price	Description
Push-on washing brush						
Push-on wash brush	1	4.113-001.0				For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M $18 \times 1.5$
Rotating washing brush						
Rotating wash brush for > 800 l/h machines, nylon bristles	2	4.113-002.0	800-1300 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to
Rotating wash brush for > 800 l/h machines, natural bristles	3	4.113-005.0	800-1300 l/h			60°C, M 18 x 1.5 (replaceable brush insert).

<sup>■</sup> Included in delivery. 

Available accessories. 

Extension hose.















		Order No.	Length	Diameter		Price	Description	
Geka coupling			'	'				
Geka connector with hose barb, R 3/4"	1	6.388-455.0					with hose liner	
Geka connector with hose barb, R 1"	2	6.388-465.0						
Geka connector with internal thread, R 1"	3	6.388-458.0					with female thread	
Suction filter								
Water suction filter	4	6.414-956.0						
Suction filter with check valve	5	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter								
Water fine filter, with adapter	6	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Water fine filter, 100 μm, R 1"	7	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	
Water supply hose								
Water supply hose	8	4.440-207.0	7.5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	9	4.440-270.0	7.5 m				NW 19 R1" / R1", up to 85 °C	

 $<sup>\</sup>blacksquare$  Included in delivery.  $\hfill\Box$  Available accessories.  $\hfill \blacktriangle$  Extension hose.