



HD 10/16-4 Cage Ex (ATEX)

Special class cold-water high-pressure cleaner designed specifically for use in potentially explosive environments.



1 Powder-coated cage frame, conductive

- Robust tubular steel frame.
- Integrated crane attachment point.

2 Explosion-proof design

- Conductive rubber tyres.
- Surface temperature always under 200 °C.



HD 10/16-4 Cage Ex (ATEX)

- Explosion protection II 2 G c T3
- Crankshaft pump with ceramic pistons
- 4-pole air-cooled electric motor

Technical data

Order Number	1.353-904.0	
EAN code	4054278157887	
Current type	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	1000
Operating pressure	bar / MPa	160 / 16
Max. pressure	bar / MPa	220 / 22
Max. water feed temperature	°C	max. 50
Power rating	kW	5,5
Weight	kg	111
Dimensions (L x W x H)	mm	980 × 720 × 1100

Equipment

High-pressure hose	m	10 / DN 8,400 bar
Spray lance	mm	1050
Power nozzle		■
Anti-twist system (AVS)		-
Pressure switch control		■
High pressure lance		■
Servo Control		-

■ Included in delivery.

ACCESSORIES FOR HD 10/16-4 CAGE EX (ATEX) 1.353-904.0



1-2

		Order Number	Nozzle size				Price	Description	
HP nozzle spray angle 0°									
High-pressure nozzle spray angle 0°	1	2.113-036.0	60					Solid jet for very stubborn dirt and stains.	■
Power nozzle spray angle 25°									
Power nozzle 25° spray angle	2	2.113-026.0	60						■

■ Included in delivery.

ACCESSORIES FOR HD 10/16-4 CAGE EX (ATEX) 1.353-904.0



		Order Number	Flow rate				Price	Description	
Trigger guns									
	1	4.118-020.0							■

■ Included in delivery.

ACCESSORIES FOR HD 10/16-4 CAGE EX (ATEX) 1.353-904.0



		Order Number	ID	Max. working pressure	Length	Price	Description
Special hoses							
High pressure hose ID 8 / 10 m leitfähig	1	6.110-064.0	ID 8	400 bar	10 m		Electrically conductive longlife high-pressure hose for use in hazardous areas with risks of explosions. Delivered with factory certification on conductivity. ■

■ Included in delivery.